

SPECIFICATION

TITLE OF THE INVENTION

COMPONENT MOUNTING APPARATUS AND METHOD, AND
COMPONENT MOUNTING EQUIPMENT

5 BACKGROUND OF THE INVENTION

The present invention relates to component mounting apparatus and method for automatically mounting a variety of components such as electronic components onto a printed circuit board or the like, and a component mounting
10 equipment including the apparatuses.

Generally, in an electronic component mounting apparatus, a number of component supply means are mounted in parallel to one another on a component supply table. In a component mounting stage, the component supply means are
15 successively positioned in a specified component supply position according to a sequence of mounting components while moving the component supply table in a direction in which the component supply means are arranged in parallel. Then, each of the components at the component supply means
20 is taken out by suction by a mounting head section, and the components are transferred to a circuit board positioned in the circuit board positioning section to be subjected to a component mounting process.

This type of conventional component mounting
25 apparatus will be described with reference to Fig. 6

09534262-032400

21

showing a perspective view of it and Fig. 7 showing a schematic plan view of it. In Fig. 6, at the front of an apparatus body 1 is provided a board positioning section 4 for positioning a circuit board P supplied from a board supply means 2 in a mounting position, and the circuit board P mounted with the required components in the board positioning section 4 is discharged by a board discharge means 3. On the other hand, at the rear of the apparatus body 1 is provided a component supply section 7, and a rotary type mounting head section 8 is provided between the component supply section 7 and the aforementioned board positioning section 4 as shown in Fig. 7.

In the component supply section 7 are laterally movably provided ~~two component supply tables 10 and 11~~ ^{10 and 11} independently of each other on a guide rail 9. The component supply tables 10 and 11 are mounted with a number of component supply means 12 arranged in parallel to one another in a direction in which the component supply tables 10 and 11 move. There is illustrated generally ^a so-called ~~the~~ parts cassette as the component supply means 12, and it will be simply described below. That is, electronic components of an identical type are stored ^{and} ~~as~~ arranged at regular intervals on a carrier tape while being wound around a reel 13 as covered with a cover tape. By drawing out the carrier tape from the reel 13 to feed it at a pitch

equal to the storage intervals of the components and taking up the cover tape, the electronic component located at the leading end is positioned in a component supply position A opposite to a component suction head 14 of the mounting head section 8.

Furthermore, as shown in Fig. 7, the mounting head section 8 is constructed by providing a plurality of component suction heads 14 at regular angular intervals on an identical circle of a rotary table (not shown) provided rotatably around a vertical axis. Each component suction head 14 is designed to suck a component by vacuum suction means. Upon intermittently rotating the rotary table, it is stopped in steps in the component supply position A and a component mounting position B in order to concurrently perform receiving of each component from the component supply means 12 and mounting of each component onto the circuit board P. While one component supply table 10 is supplying components, the other component supply table 11 that is retreating in a standby position performs changing of component supply means 12 and replenishing of components thereby achieving preparation so that the component mounting apparatus can be operated *continuously* incessantly.

In recent years, there has been a growing trend *in* that the types of circuit boards P to be manufactured and the types of components to be mounted on the circuit boards

a
0043
a
a
a
a
00432ED"2924E560
P are increasing. In order to cope with the above, ~~it can~~
~~be considered~~ to increase the number of component supply
means 12 to be mounted ^{on} the component supply tables 10
and 11. However, in such a case, the component supply
5 tables 10 and 11 are to be elongated sidewise ^{in order} according to
the increase in number of ^{the} component supply means 12 to
~~be mounted~~. Consequently, the length of the entire
component supply section 7 becomes very long, and this
leads to a degraded space utilization efficiency, reducing
10 the productivity per floor area.

A more important issue is that the component
supply tables 10 and 11 are fed at a pitch in accordance
with taking out the components by the mounting head section
8, and therefore, the following inconvenience occurs. That
15 is, when the component supply tables 10 and 11 increase in
weight ^{due} according to the increase of their lengths, not only
a great ^{is} drive power ^{is} required to move the component
supply tables 10 and 11 but also the inertial force of the
component supply tables 10 and 11 increases. Therefore,
20 vibration in feeding the component supply tables 10 and 11
at a pitch significantly increases. Consequently, it is
impossible to increase the component supply rate, or the
component mounting operation speed.

SUMMARY OF THE INVENTION

25. Accordingly, it is an object of the present

a
invention to provide ^a component mounting apparatus and
method capable of increasing the component mounting
operation speed without dimensionally increasing the whole
apparatus even when the types of boards and the number of
5 components to be mounted on each board increase ~~and a~~
~~component mounting apparatus employing the apparatus.~~

a
In accomplishing these and other objects,
according to a first aspect of the present invention, there
is provided a component mounting apparatus comprising:

10 a pair of component supply tables on which
components are accommodated and which are arranged on both
sides of a board mounting position where a board is
positioned;

15 a first mounting head section for successively
picking up the components at one of the component supply
tables and thereafter successively mounting the picked-up
components onto the board; and

20 a second mounting head section for successively
picking up the components at the other of the component
supply tables and thereafter successively mounting the
picked-up components onto the board,

wherein the first and second mounting head sections
are independently operated.

According to a second aspect of the present
25 invention, there is provided the component mounting

004220"2924560

a

apparatus as ^{described} claimed in the first aspect, wherein the first and second mounting head sections are controlled mutually in operation in accordance with a timing at which, when one of them carries out a component picking-up operation for
5 picking up the components from the component supply table, the other of them carries out a component mounting operation for mounting the picked-up components onto the board.

According to a third aspect of the present
10 invention, there is provided the component mounting apparatus as ^{described} claimed in the first aspect, wherein one of the first and second mounting head section has component suction nozzles sucking the components at one time.

According to a fourth aspect of the present
15 invention, there is provided the component mounting apparatus as ^{described} claimed in the second aspect, wherein one of the first and second mounting head section has component suction nozzles sucking the components at one time.

According to a fifth aspect of the present
20 invention, there is provided a component mounting equipment comprising:

2nd 4

a plurality of component mounting apparatuses each of which ~~is claimed in~~ the first aspect,
194
wherein a board transfer path along which the board is
25 supplied to the board mounting position of the apparatus

09534262.032400

and discharged from the board mounting position of the apparatus by a board transfer device is provided so that the board transfer path connects the board mounting positions of the component mounting apparatuses, and the component supply tables of the component mounting apparatuses are arranged on both sides of the board mounting positions in the board transfer path.

According to a sixth aspect of the present invention, there is provided a component mounting equipment comprising:

a plurality of component mounting apparatuses each of which ~~is claimed in~~ the second aspect,

wherein a board transfer path along which the board is supplied to the board mounting position of the apparatus and discharged from the board mounting position of the apparatus by a board transfer device is provided so that the board transfer path connects the board mounting positions of the component mounting apparatuses, and the component supply tables of the component mounting apparatuses are arranged on both sides of the board mounting positions in the board transfer path.

According to a seventh aspect of the present invention, there is provided the component mounting equipment as ~~claimed~~ ^{described} in the fifth aspect, wherein the components to be mounted onto the single board are all

distributed into groups by type, and the components of the groups are accommodated in the component supply tables of the component mounting apparatuses as assigned thereto.

a

09534232-032400

According to an eighth aspect of the present invention, there is provided the component mounting equipment as ^{described} claimed in the sixth aspect, wherein the components to be mounted onto the single board are all distributed into groups by type, and the components of the groups are accommodated in the component supply tables of the component mounting apparatuses as assigned thereto.

According to a ninth aspect of the present invention, there is provided a component mounting method comprising steps of:

15 picking up by a first mounting head section components from one of a pair of component supply tables on which the components are accommodated and which are arranged on both sides of a board mounting position where a board is positioned, the first mounting head section successively picking up the components at one of the component supply tables;

20 thereafter successively mounting the components picked up by the first mounting head section onto the board;

picking up by a second mounting head section components from the other of the pair of component supply

25

tables, the second mounting head section successively picking up the components at the other of the component supply tables; and

thereafter successively mounting the components
5 picked up by the second mounting head section onto the board,

wherein the picking-up and mounting steps of the first mounting head section and the picking-up and mounting steps of the second mounting head section are independently
10 carried out.

According to a tenth aspect of the present invention, there is provided the component mounting method as ~~claimed~~ *described* in the ninth aspect, wherein the picking-up step of the first mounting head section and the mounting step of
15 the second mounting head section are carried out at the same time, and the mounting step of the first mounting head section and the picking-up step of the second mounting head section are carried out at the same time.

According to an eleventh aspect of the present
20 invention, there is provided the component mounting method as ~~claimed~~ *described* in the ninth aspect, wherein in a component mounting equipment comprising a plurality of component mounting apparatuses each of which comprises the first and second mounting head sections and the pair of component
25 supply tables between which a board transfer path along

004230-2924E560

a

a

which the board is supplied to the board mounting position of the apparatus and discharged from the board mounting position of the apparatus by a board transfer device is provided so that the board transfer path connects the board mounting positions of the component mounting apparatuses, and the component supply tables of the component mounting apparatuses are arranged on both sides of the board mounting positions in the board transfer path,

the picking-up and mounting steps of the first mounting head section and the picking-up and mounting steps of the second mounting head section are sequentially carried out.

According to a twelfth aspect of the present invention, there is provided the component mounting method as ~~claimed~~ ^{described} in the eleventh aspect, wherein the picking-up step of each of the first mounting head sections and the mounting step of each of the corresponding second mounting head sections are carried out at the same time, and the mounting step of each of the first mounting head sections and the picking-up step of each of the corresponding second mounting head sections are carried out at the same time.

According to a thirteenth aspect of the present invention, there is provided the component mounting equipment as ~~claimed~~ ^{described} in the eleventh aspect, wherein the components to be mounted onto the single board are all

004422-032400

A

A

distributed into groups by type, and the components of the groups are accommodated in the component supply tables of the component mounting apparatuses as assigned thereto.

According to a fourteenth aspect of the present invention, there is provided the component mounting equipment as ~~claimed~~ ^{described} in the twelfth aspect, wherein the components to be mounted onto the single board are all distributed into groups by type, and the components of the groups are accommodated in the component supply tables of the component mounting apparatuses as assigned thereto.

With the above arrangement, the component supply table is installed fixedly, and therefore, it becomes free of vibration regardless of the number of mounted component supply means which can be mounted thereon. The mounting head section is a robot type which sucks a plurality of components from the component supply table at one time and thereafter successively mounts the components to specified portions of the board. Therefore, even when the number of components to be mounted on a board increases, the component mounting operation speed can be remarkably increased further than in the conventional apparatus in which the component supply table is fed at a pitch with respect to the rotary type mounting head section.

Furthermore, components can be mounted by the two of the first and second mounting head sections onto the

004260"2927E560

a

board positioned in a single board mounting position, and therefore, the component mounting operation speed can be further increased.

With the above arrangement of the fifth and sixth
5 aspects and the eleventh and twelfth aspects, by mounting
different components on the component supply tables
installed at each of the component mounting apparatuses,
the component supply tables are inevitably arranged on both
sides of the board transfer path along it even when the
10 types and the number of components to be mounted onto the
board increase. Therefore, the equipment does not
dimensionally increase as a whole without expanding
significantly in the direction of the board transfer path.
Furthermore, the mounting head sections of the component
15 mounting apparatuses operate at high speed and the
component supply tables are fixedly installed, and
therefore, the component mounting operation speed can be
increased.

With the above arrangement of the thirteenth and
20 fourteenth aspects, when the types of boards are increased,
the equipment can cope with it only by replacing a
specified one of the component supply tables installed at
the respective component mounting apparatuses with a
component supply table mounted with components of the
25 required type.

004220-2944560

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of the present invention will become clear from the following description taken in conjunction with the preferred
5 embodiments thereof with reference to the accompanying drawings, in which:

Fig. 1 is a schematic plan view schematically showing ~~a~~ component mounting equipment according to an embodiment of the present invention;

10 Fig. 2 is a perspective view of an embodiment of the component mounting apparatus of the present invention, the apparatus being a part of the above equipment;

Fig. 3 is a plan view of an operating mechanism section of the above apparatus;

15 Fig. 4 is a flow chart of the above apparatus;

Fig. 5 is a block diagram showing construction for performing the control operation of the apparatus;

Fig. 6 is a perspective view of a conventional component mounting apparatus; and

20 Fig. 7 is a schematic plan view of the above conventional apparatus.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Before the description of the present invention proceeds, it is to be noted that like parts are designated
25 by like reference numerals throughout the accompanying

a
00534262-032400

drawings.

An embodiment of the present invention will be described below with reference to Figs. 1 through 4.

a

Fig. 1 is a schematic plan view schematically showing a component mounting equipment (component mounting line) according to an embodiment of the present invention. In the figure, four component mounting apparatuses 27A through 27D are provided along a board transfer path 21, and four board transfer means 22 are provided for the component mounting apparatuses 27A through 27D along the board transfer path 21 in the lateral direction so that each board transfer means 22 supplies a board to be mounted with components to a board mounting position of one of the component mounting apparatuses and discharges the board therefrom. The component mounting apparatuses 27A through 27D have an identical basic structure, and therefore, the component mounting apparatus 27D is taken as an example to be described below with reference to Fig. 2 that shows a perspective view of it and Fig. 3 that shows a plan view of its operating mechanism section.

In the component mounting apparatus 27D shown in Fig. 2, a laterally provided pair of inverted U-shaped support frames 29 are arranged in parallel to each other along the board transfer path 21 while allowing the board transfer path 21 to penetrate them. Between both the

a

support frames 29 are arranged two operating frames 30 in parallel to each other across the frames 29, ^{29. the operating frames} and they are supported individually movably in a direction perpendicular to the board transfer path 21. To each operating frame 30 is mounted a mounting head section 31 movably along the operating frame 30. At the mounting head section 31, four component suction nozzles 33 are provided at regular intervals (at intervals of 90°) around a rotary member 32 that is rotatably supported around a horizontal axis. Upon rotating the rotary member 32 at a pitch equal to each interval of the component suction nozzles 33, the component suction nozzles 33 are selectively and sequentially directed downward to suck a component 34 from a component supply table 28A and mount the sucked component 34 onto a circuit board 37 located at the board mounting position where the board 37 is positioned by a board positioning section 24.

Between both the support frames 29 are inserted the component supply tables 28A from both depthwise sides as moved by casters 40, and thereafter they are fixedly installed in specified positions. The component supply table 28A is provided with component supply means 12 comprised of parts cassettes provided with the aforementioned reels 13. Other than this, as shown in Fig. 1, a component supply table 28B mounted with a stick-shaped

component supply means 38 at which components stored in a pipe member are successively fed to a take-out position, a component supply table 28C on which bulk components 39 are placed, and a tray-shaped component supply table 28D are
5 installed at the component mounting apparatuses 27A through 27D. It is to be noted that the tray-shaped component supply table 28D is provided with a mounting head section 59 having a pivot arm shape for taking out the components thereof.

10 In Fig. 3, each operating frame 30 houses therein a head positioning mechanism section 41 for moving the mounting head section 31 in the lengthwise direction of the board transfer path 21.

004220"2924560
The head positioning mechanism section 41 is
15 comprised of a ball thread 43 that is rotatably supported across a pair of support plates 42 fixed to both ends of each operating frame 30, a step motor 47 for rotatively driving the ball thread 43 via a connecting means 44, and a moving member 49 in which a nut 48 meshed with the ball
20 thread 43 is internally fixed and moved in accordance with the rotation of the ball thread 43. The mounting head section 31 is fixed to the moving member 49 via a head holder 50, and the head holder 50 is internally provided with a known head elevation mechanism section 51 for
25 vertically moving the mounting head section 31.

Each of the support frames 29 houses therein a head feed mechanism section 52 for moving the head positioning mechanism section 41 via each operating frame 30 in a direction perpendicular to the board transfer path 21. The head feed mechanism section 52 is comprised of a ball thread 54 that is rotatably supported across a pair of support plates 53 fixed to both ends of each support frame 29, a step motor 56 for rotatively driving the ball thread 54 via a connecting means 55, a moving member 57 that is fixed to an end portion of each operating frame 30 as meshed with the ball thread 54 and operates to move the operating frame 30 in accordance with the rotation of the ball thread 54, and a guide shaft 58 that is fixed across the support plates 53 and operates to slidably support the operating frame 30 while allowing the guide shaft 58 to penetrate the other end of the operating frame 30. A controller 100 controls the operations of the apparatuses 27A-27D and the board transfer means 22, because it is connected to them as shown in Fig. 5 in which the connection structure of the apparatus 27B is shown as one example. The other connection structure of the apparatuses 27A, 27C, and 27D are similar to the apparatus 27B.

The operation of the aforementioned component mounting equipment will be described next with reference to a flowchart of Fig. 4. In the component mounting

apparatuses 27A through 27D, the mounting head sections 31 are controlled in accordance with a timing at which, while one mounting head section 31 is sucking components 34 from one of the component supply tables 28A through 28D, the other mounting head section 31 mounts the components 34 onto the circuit board 37. Since both the mounting head sections 31 execute an identical operation except for an operating timing shift, only the operation of one mounting head section 31 will be now described.

10 First, the mounting head section 31 is moved to a position just above the component 34 to be sucked by suction on one of the component supply tables 28A through 28D and then positioned (step S1). That is, upon rotating the step motor 47 of the head positioning mechanism section 15 41 by a specified angle in the required rotational direction, the moving member 49 moves in the lengthwise direction of the board transfer path 21 by the ball thread 43 that is rotating integrally with the step motor 47, and the mounting head section 31 is moved to a specified component take-out position on the one of the component 20 supply tables 28A through 28D. In this stage, in regard to the other component supply tables 28A through 28C except for the tray-shaped component supply table 28D, the component take-out position is positioned in a straight 25 line extending along the board transfer path 21.

004230-294450

Consequently, the mounting head section 31 does not move as positioned in the position until such components as the parts cassette or the stick fronting the mounting head section 31 deplete.

5 When the mounting head section 31 is positioned, the head elevation mechanism section 51 operates to move down the mounting head section 31, the component suction nozzle 33 sucks a component 34, and thereafter the mounting head section 31 is slightly moved up by the head elevation
10 mechanism section 51 (step S2). Subsequently, the rotary member 32 of the mounting head section 31 is rotated by one pitch, and the next component suction nozzle 33 is made to front the component take-out position (step S3). In this stage, it is decided whether or not the mounting head
15 section 31 has completed the suction of a specified number (four in this embodiment) of components 34 (step S4). ~~When~~ it has not been completed, the same operation as above will be repeated to suck the specified number of components 34.

When the suction of the specified number of
20 components 34 has been completed, the step motor 56 of the head feed mechanism section 52 and the step motor 47 of the head positioning mechanism section 41 are simultaneously driven to move the mounting head section 31 onto the board positioning section 24 via the operating frame 30 in
25 accordance with the rotation of the ball thread 54 and then

00534262-032400

a

position it just above a specified component mounting position of the circuit board 37 by the head positioning mechanism section 41 (step S5). Then, the head elevation mechanism section 51 is driven to mount the components that have been held by the component suction nozzle 33 as sucked thereto onto the circuit board 37 (step S6). After the mounting head section 31 is slightly moved up by the head elevation mechanism section 51, the mounting head section 31 is moved to a position just above the next component mounting position of the circuit board 37 and then positioned by the operations of the head positioning mechanism section 41 and the head feed mechanism section 52, and the rotary member 32 is rotated by one pitch, so that the component to be mounted next is made to front the component mounting position (step S7).

In this stage, it is decided whether or not the mounting of all the components 34 that have been held by the mounting head section 31 as sucked thereto has been completed (step S8). *it* When it has not been completed, the same operation as above will be repeated to mount all the components 34 onto the specified positions of the circuit board 37.

When the specified number of components has been completed at step S8, it is decided whether or not the mounting of all the components 34 distributed to the

004220"2924560

a

a

004250-234550

a

5 component mounting apparatuses 27A through 27D for the circuit board 37 positioned in the board positioning section 24 has been completed (step S9). ~~When~~ it has not been completed, the mounting head sections 31 are moved

10 again above the component supply tables 28A through 28D to repeat the suction of the components 34 from the component supply tables 28A through 28D and the mounting of the components 34 onto the circuit board 37 in a manner similar to the above until the mounting of all the components 34

15 onto the circuit board 37 ~~will~~ ^{is} complete. ^d When the mounting of all the components 34 onto the circuit board 37 is completed, each circuit board 37 positioned in the board transfer path 21 is fed by a specified pitch to be positioned in the board positioning sections 24 of the

20 component mounting apparatuses 27A through 27D for the next process (step S10), and an operation similar to the above will be repeated.

25 In the above component mounting equipment, mutually different components can be mounted on the component supply tables 28A through 28D of the plurality (four in this embodiment) of component mounting apparatuses 27A through 27D provided in parallel to one another along the board transfer path 21. Therefore, when the types and the number of components 34 to be mounted onto the circuit board 37 increase, these components are mounted on the

component supply tables 28A through 28D as distributed into groups classified by type. With this arrangement, since the component supply tables 28A through 28D are mounted with only the components 34 of the respective groups, the
5 tables are not dimensionally increased. Furthermore, since the component supply tables 28A through 28D are installed perpendicularly to the board transfer path 21 at the component mounting apparatuses 27A through 27D, the equipment is not dimensionally increased as a whole without
10 significantly expanding in the direction of the board transfer path 21.

Furthermore, since the mounting head section 31 of the component mounting apparatuses 27A through 27D only operates and the component supply tables 28A through 28D
15 are fixedly installed, the tables become free of vibration regardless of the number of mounted component supply means 12 and 38. Furthermore, the mounting head section 31 sucks at one time a plurality of components 34 from the component supply tables 28A through 28D and successively mounts the
20 components 34 onto the specified portions of the circuit board 37. Furthermore, the component mounting apparatuses 27A through 27D are each provided with a pair of mounting head sections 31 and controls the mounting head sections 31 so that, while one is sucking components 34, the components
25 34 that are held by the other as sucked thereto are mounted.

004220-292456

to the circuit board 37. With the above arrangement, even when the types and the number of components 34 to be mounted onto the circuit board 37 increase, the component mounting operation speed can be remarkably increased further than in the conventional apparatus in which the component supply table is fed at a pitch with respect to the rotary type mounting head section.

When the types of circuit boards 37 increase, it can be coped with only by replacing a part of the component supply tables 28A through 28D installed at the component mounting apparatuses 27A through 27D with component supply tables 28A through 28D mounted with required components 34. It is to be noted that the component mounting apparatuses 27A through 27D can be also used singly.

According to the present invention as described above, there is provided a robot type mounting head section in which the component supply tables are installed fixedly, and a plurality of components are sucked at one time from the component supply tables and thereafter transferred to be successively mounted onto the specified portions of the board. With this arrangement, even when the number of components to be mounted onto the board increases, the component mounting operation speed can be remarkably increased further than in the conventional structure in which the component supply table is fed at a pitch with

004220" 2924550

respect to the rotary type mounting head section. Furthermore, since the laterally provided pair of first and second mounting head sections are mutually controlled in operation in accordance with a timing at which, when one is
5 located on the component supply table, the other is located on the board positioning section. With this arrangement, components can be mounted onto ^a single board by a plurality of mounting head sections, and therefore, the component mounting operation speed can be further increased.

10 Furthermore, according to the component mounting equipment of the present invention, by mounting mutually different components onto the component supply tables of the component mounting apparatuses arranged in parallel to one another, even when the types and the number of
15 components to be mounted onto the circuit board increase, the equipment is not dimensionally increased as a whole without significantly expanding in the direction of the board transfer path. Furthermore, the component mounting operation speed can be further increased. In this case,
20 there may be provided the structure in which all the components to be mounted onto single board are distributed into groups by type and the components of each group are mounted on component supply tables as assigned to them installed at the respective component mounting apparatuses.
25 With this arrangement, when the types of boards increase,

001210-292450

a

it can be coped with only by replacing a part of the component supply tables of the component mounting apparatuses with component supply tables mounted with the required components.

5 Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and
10 modifications are to be understood as included within the scope of the present invention as defined by the appended claims unless they depart therefrom.

004250-2924550